

# Technical Data Sheet



**Product:** AS-21000 Series Cable Anchor Sling



PeakWorks Anchor Slings are offered in a variety of materials and lengths to satisfy the needs of industry. Each part is thoroughly tested during the product development stage and is batch tested to confirm conformance. All PeakWorks Anchor Slings have a minimum tensile strength of 5000 lbs.

**Length:** 4 ft, 6 ft

**Material:** PVC (transparent red) coated aircraft cable, Galvanized 7x19 strands

**Minimum Breaking Strength:** 5,000 lbs (22.2 kN)

**Number of Workers:** 1

**Weight:** 1 lb (0.45 kg)

**Capacity:** 140 kg (310 lbs) for one worker (combined weight of person, tools, clothing, etc)

**Operating Temperature:** -35° C to +35° C

## STANDARDS

**Compliance:** ANSI Z359.1-92 (Anchorage Connector Components) & OSHA requirements.

**Component Compatibility:** PeakWorks anchor slings are designed for use with PeakWorks approved components or subsystems (full body harnesses, lifelines, rope grabs, connectors, self retracting lifelines, etc.) or as recommended by a Qualified Person.

**Warnings:** See Operating and Maintenance Instruction Manual for details.

**Storage:** Store in a cool dry place away from chemicals, water, corrosive environments, and sources of heat or spark.