

Technical Data Sheet



Product: RAS2 Series Residential Anchor Sling



PeakWorks Anchor Slings are offered in a variety of materials and lengths to satisfy the needs of industry. Each part is thoroughly tested during the product development stage and is batch tested to confirm conformance. All PeakWorks Anchor Slings have a minimum tensile strength of 5000 lbs. The **RAS2** has the addition of a wear pad added to the loop areas to provide additional wear resistance as well as creating a narrower point for hook attachment.

Length: 3 ft, 4 ft

Material: 2" (61 mm) Natural Polyester Tie-down Webbing

Minimum Breaking Strength: 5,000 lbs (22.2 kN)

Number of Workers: 1

Weight: 0.5 lbs (0.23 kg)

Capacity: 140 kg (310 lbs) for one worker (combined weight of person, tools, clothing, etc)

Operating Temperature: -35° C to +35° C

STANDARDS

Compliance: ANSI Z359.1-92 (Anchorage Connector Components) & OSHA requirements.

Component Compatibility: PeakWorks anchor slings are designed for use with PeakWorks approved components or subsystems (full body harnesses, lifelines, rope grabs, connectors, self retracting lifelines, etc.) or as recommended by a Qualified Person.

Warnings: See Operating and Maintenance Instruction Manual for details.

Storage: Store in a cool dry place away from chemicals, water, corrosive environments, and sources of heat or spark.