

Technical Data Sheet



Product: RG-11010 Rope Grab



PeakWorks RG-11010 Rope Grab is designed for use with 5/8" (16 mm) rope. There is a Panic Grab feature built into the device to ensure the arrest of a fall even if the user pushes the cam upward in a panic situation. Each part is thoroughly tested during the product development stage and is batch tested to confirm conformance.

Connecting Component: 1 1/4" Ring

Material: Steel with a corrosion resistant plating

Minimum Breaking Strength: 5,000 lbs (22.2 kN)

Number of Workers: 1

Weight: 2.0 lbs (.90 kg)

Capacity: 136 kg (30 lbs) for one worker (combined weight of person, tools, clothing, etc)

Operating Temperature: -35° C to +35° C

STANDARDS

Compliance: Certified to CSA Z259.2.1-98(R2004) & ANSI Z359.1-2007

Component Compatibility: Are designed for use with 5/8" (16 mm) rope and PeakWorks approved components or subsystems (full body harnesses, lifelines, rope grabs, connectors, self retracting lifelines, etc.) or as recommended by a Qualified Person.

Warnings: See Operating and Maintenance Instruction Manual for details.

Storage: Store in a cool dry place away from chemicals, water, corrosive environments, and sources of heat or spark.